



# Premium Elastomeric Driveway Crack Sealant

## Polymer Modified Asphalt Emulsion Based Crack Sealant

- Elastomeric Formula for Outstanding Flexibility & Adhesion
- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- High Solids Formula for Lasting Repair
- Dries Black



Revised: 08/17

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

A polymer modified elastomeric asphalt emulsion crack sealant designed for sealing cracks up to 3/4" wide in asphalt pavement surfaces.

### Uses

- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

### Surface Preparation

Proper preparation of the crack to be treated is vital to ensuring maximum performance. Use a stiff brush to remove all loose material, dirt, oil, vegetation and existing sealants. Cracks deeper than 1" should be filled with backer-rod or a suitable material to 1/2" depth

### Application

JETCOAT Premium Elastomeric Driveway Crack Sealant is packaged ready to use. Cut tip of spout to desired width and puncture seal. Apply material into crack with caulking gun.

### Drying Time

Allow Crack Filler to cure for 24-48 hours prior to sealing or opening to traffic.

### Clean Up

- While wet, use soap and water.
- When Dry, kerosene or mineral spirits.

### Weather Conditions

- Apply when temperatures are expected to be above 50 °F for at least 48 hours.
- Do not apply when rain is imminent within 48 hours.

### Coverage (Approximate)

- One 10 ounce tube will fill approximately 6-12 feet of cracks. Ultimate coverage will be dependent upon depth and width of cracks.

### Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

This product does not contain any California Proposition 65 Chemicals.

Premium Elastomeric Driveway Crack Sealant  
Polymer Modified Asphalt Emulsion Based Crack Sealant

Form No.: JC-TD23749

## Packaging

Item #	Container Size	Pack	Weight
23749	10 Oz. Tube	12	10.1 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Clay	1332-58-7
Polymer Latex	Proprietary
Water	7732-18-5