



Premium Rubberized Foundation & Roof Coating

Polymer-Modified Asphalt Emulsion For Superior Waterproofing

- Seals Out Water & Moisture
- Advanced Elastomeric Formula Bridges Hairline Cracks in Concrete
- Easy to Apply
- Soap & Water Cleanup
- Zero Voc Water-Based Formula



Revised: 08/17

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

An elastomeric polymer modified asphalt emulsion designed for coating concrete foundations, roofs, & more. Protects concrete foundations & roofs from moisture and water intrusion. Dries black.

Uses

- Most Roof Surfaces
- Waterproofing Exterior Concrete
- Basement Walls
- Poured Concrete Walls
- Polystyrene/Styrofoam Insulation Board
- Wood, Foam & More

Surface Preparation

For best results, surface shall be clean, dry and free of any dirt or contaminants.

Application

Stir container thoroughly. Apply using either a brush, trowel, or airless spray unit (suggested tip size .021 to .025). Apply material at a rate of 150 square feet per 4.75 gallon pail. Allow material to dry and cure for 24 hours prior to application of foam or drainage boards or backfilling.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

While wet, use soap and water.

Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Approximately 150 square feet per 4.75 gallon pail at 60 mils thickness.

Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 0 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

CALIFORNIA PROPOSITION 65 CHEMICAL WARNING:

This product contains chemicals known to the state of California to cause birth or developmental defects.

Premium Rubberized Foundation & Roof Coating
Polymer-Modified Asphalt Emulsion For Superior Waterproofing

Form No.: JC-TD64105

Packaging

Item #	Container Size	Pack	Weight
64105	4.75 Gallon Pail	1	42 lbs.
64101	.9 Gallon Pail	6	52 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Polymer	N/A
Asphalt	8052-42-4