



Premium Asphalt Fence Paint

Penetrates, Preserves & Protects

- Apply by Brush, Spray or Roller
- Penetrates, Preserves & Protects
- Livestock Safe - Dry Finish
- Meets ASTM D 4479



Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

Asphalt based fence paint fortified with special oils designed to penetrate, preserve and protect wood and other types of surfaces. It will also add years of service life as it rust proofs metal, preserves wood, damp proofs stone or brick and rejuvenates composition surfaces. Helps prevent cribbing on fencing and stalls. Designed for use above or below grade.

Uses

- Wood or Metal Fences & Posts
- Masonry & Concrete
- Use Above or Below Grade

Surface Preparation

Surface shall be clean, dry and free of any dirt or contaminants.

Application

Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size .017 to .023). Although paint will cover in one coat, a second coat may be applied for optimum performance and durability.

Drying Time

Up to 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits in well ventilated area immediately after use.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Up to 200 square feet per gallon
- Up to 1,000 square feet per 4.75 gallon pail

Precautions

- Do Not Heat Or Thin
- Do Not Store Container At Temperatures Above 100 ° F
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out Of Reach Of Children



Premium Asphalt Fence Paint
Penetrates, Preserves & Protects

Form No.: JC-TD66445

Packaging

Item #	Container Size	Pack	Weight
66445	4.75 Gallon Pail	1	49 lbs.
66441	.9 Gallon Pail	6	59 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7