



Concrete Sealer

Professional Grade 100% Acrylic Emulsion

- Seals & Protects
- Weatherproofs
- Dustproofs
- Water-Based
- Clear Finish
- Cures Concrete
- Salt & Chemical Resistant



Manufacturer:

JETCOAT
 472 Brehl Avenue
 Columbus, Ohio
 Phone: 800-394-0047
 Fax: 614-279-7201
 www.JETCOATinc.com

Description

JETCOAT Concrete Sealer is a professional grade 100% Acrylic water-based clear drying emulsion. It is designed to seal and protect both interior and exterior concrete surfaces.

Uses

- Driveways, Patios, Sidewalks, Pool Decks, Floors, Quarry Tiles, Paver Bricks, Brick Surfaces, Masonry, & More.

Surface Preparation

- **Clean Concrete Surface** - Sweep all dirt and loose debris from concrete surface. Scrub all oil and gasoline stains with household detergent and water. Rinse off entire concrete surface with water and allow to dry thoroughly before applying concrete sealer.
- **Clean and Fill Cracks** - Remove dirt and vegetation from cracks with screwdriver, wire brush or other suitable instrument. Clean out cracks with hose and water and allow to dry. Fill cracks up to 1/2" wide with JETCOAT Pourable Concrete Crack Sealant. Fill larger cracks up to 1" wide with JETCOAT Concrete Patch. Allow crack filler or patch to dry 24 hours prior to applying JETCOAT Concrete Sealer.

Application

Stir pail thoroughly. JETCOAT Concrete Sealer is ready-to-use. Do not dilute. Apply a thin even coat of concrete sealer with a roller, brush, or garden type sprayer. For best results apply at a rate of 200

square feet per gallon per coat. Additional coats may be applied to create a higher gloss surface.

Drying Time

Allow 2-3 hours to dry, depending on weather conditions.

Clean Up

- Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24- hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- For best results apply JETCOAT Concrete Sealer at a rate of 200 square feet per gallon (950 square feet per 4.75 gallon pail).

Precautions

- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F



Concrete Sealer
Professional Grade 100% Acrylic Emulsion

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Packaging

Item #	Container Size	Pack	Weight
66595	4.75 Gallon Pail	1	46 lbs.
66591	.9 Gallon Pail	6	55 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	Proprietary