

## ONE-COAT COLOR

### 100% acrylic coating for tennis, basketball, pickleball, & multi-purpose courts

- Exceptional Durability and fade resistance
- Safe Non-Slip surface
- Water-Based
- Vibrant Finish

#### MANUFACTURER

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio 43223  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

#### DESCRIPTION

Surface 1 One-Coat Color is a 100% acrylic coating for tennis, basketball, pickleball and multi-purpose courts and recreational areas. Surface 1 One-Coat Color is fortified with sand to provide a safe, non-slip surface. Our revolutionary formula provides superior hiding and durability with only one coat.

#### AVAILABLE COLORS

- Light Green
- Medium Green
- Dark Green
- Red
- Blue
- Gray

#### SURFACE PREPARATION

New asphalt must cure a minimum of 14 days and new concrete must cure a minimum of 30 days prior to application.

Concrete surfaces must have a medium broomed finish (if concrete has a smooth finish you will need to shot blast to get a textured surface). Concrete must be acid etched. Prime concrete prior to application with Surface 1 Patch Binder (1 part Patch

Binder to 1 part water). Priming is recommended on new concrete or old oxidized surfaces.

Clean Surface - Sweep all dirt and loose debris from surface. Scrub all oil and gasoline stains with household detergent and water. Rinse off entire surface with water and allow to dry thoroughly before applying Surface 1 one Coat Color.

Clean and Fill Cracks - Remove dirt and vegetation from cracks with screwdriver, wire brush or other suitable instrument. Clean out cracks with hose and water and allow to dry. Fill cracks up to 1" wide with Surface 1 Acrylic Crack Filler.

Allow crack filler to dry prior to applying Surface 1 One Coat Color (dry time varies depending on width and depth of crack).

#### MIXING

Stir material thoroughly before using. Do not dilute. A drill and paddle mixer is recommended to ensure complete mixing of product. The recommended minimum is a 9 amp mud-mixer type drill.

#### APPLICATION

Apply Surface 1 One-Coat Color with a soft rubber squeegee (50-60 durometer recommended for squeegee rubber softness). Although Surface One is a one coat product, multiple coats may be necessary to fill surface voids, change color schemes, and achieve a longer-lasting surface. Allow each coat to dry completely before applying additional coats or lines.

#### DRYING TIME

Drying time is dependent on temperature, shade, humidity, etc. (1 to 4 hours of dry time per coat can be expected).

#### CLEAN UP

Wash tools in water before material dries.

### **WEATHER CONDITIONS**

Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.

In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.

Do not apply if rain is imminent or forecast within 24 hours of application.

### **COVERAGE (APPROXIMATE)**

1 gallon will cover approximately 60-75 sq. ft., depending on pavement porosity (300-375 sq. ft. per 5 gallon pail).

### **PRECAUTIONS**

Do Not Freeze. Do Not Store At Temperatures Below 50 °F.

### **CAUTION**

KEEP OUT OF REACH OF CHILDREN. Protect from freezing. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. Store material with container tightly closed and upright to avoid spillage. Do not store material in direct sunlight or in areas exceeding 100 degrees Fahrenheit. In case of spill, absorb and dispose of in accordance with Federal, State, and local regulations.

### **LIMITED WARRANTY**

JETCOAT warrants this product to be of merchantable quality, when used or applied in accordance with the instructions hereon. JETCOAT does not warrant this product to be suitable for any particular use or purpose other than for which it is intended. Liability is limited to replacement of the product, or at its option, to a refund of the price thereof. There are no other warranties either

expressed or implied. Liability for any incidental or consequential damage or loss is specifically excluded at all times.