



# Standard Pourable Driveway Crack Filler

## Asphalt Emulsion Based Crack Filler

- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- Easy to Apply
- Dries Black



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An asphalt emulsion crack filler designed for sealing cracks up to 1/2" wide in asphalt pavement surfaces.

### Uses

- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

### Surface Preparation

For best results, clean all cracks free of dust, dirt, and debris by broom, water spray or power blower. Assure all cracks are free of water, vegetation and existing crack filler. Cracks deeper than 1" should be filled with backer-rod or a suitable material to 1/2" depth.

### Application

JETCOAT Standard Pourable Driveway Crack Filler is packaged ready to use. Shake container well before use. Cut spout tip to accommodate crack size. Place spout above crack, squeeze out crack filler while drawing spout along crack. Keep material in crack, at or below surface, since crack filler remains flexible. Over application may cause scuffing and tracking. A second application can be made if necessary. Allow 24 hours between applications.

### Drying Time

Allow Crack Filler to cure for 24-48 hours prior to sealing or opening to traffic.

### Clean Up

- While wet, use soap and water.
- When Dry, kerosene or mineral spirits.

### Weather Conditions

- Apply when temperatures are expected to be above 50 °F for at least 48 hours.
- Do not apply when rain is imminent within 48 hours.

### Coverage (Approximate)

- Depending on size and depth of cracks, approximate coverage is 100 lineal feet per gallon for cracks 1/2" wide and 1/4" deep.

### Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

**Standard Pourable Driveway Crack Filler**  
Asphalt Emulsion Based Crack Filler

Form No.: JC-TD23701

## Packaging

Item #	Container Size	Pack	Weight
23701	.9 Gallon	6	62.3 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Hydrous Aluminum Silicate	1332-58-7
Quartz	14808-60-7
Calcium Sulfate	10101-41-4
Biocides	55406-53-6
Water	7732-18-5