



Acrylic Oil Spot Primer

Polymer Modified Emulsion Stain Sealer



- Seals & Primes Oil & Grease Spots on Asphalt Driveways
- Improves Adhesion of Driveway Sealer
- Reduces Oil Spot Bleed-Through

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A polymer modified emulsion designed to seal oil and gasoline stains prior to applying JETCOAT Driveway Sealers or Resurfacers. Dries clear.

Uses

- Priming Oil & Gas Stains on Asphalt Pavement Prior to Applying Driveway Sealer

Surface Preparation

For best results, scrub oil and grease stains with stiff brush or broom, household detergent, and water. Rinse thoroughly with water.

Application

Mix contents of container by moderate shaking. Apply oil spot primer to stained areas. Spread with paint brush or other suitable brush. A second coat of oil spot primer may be applied for added bleed-through resistance. Oil Spot Primer must be completely dry before applying driveway sealer.

Drying Time

Typically, drying time is 1-2 hours.

Clean Up

- While wet, use soap and water.
- When dry, use paint thinner.

Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature

is expected to drop below 60 °F within a 24 hour period.

Coverage (Approximate)

- One .9 quart will cover approximately 30-50 square feet (one coat).

Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

Acrylic Oil Spot Primer
Polymer Modified Emulsion Stain Sealer

Form No.: JC-TD23744

Packaging

Item #	Container Size	Pack	Weight
23744	.9 Quart Bottle	12	28.5 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Polymer Latex	Proprietary
Water	7732-18-5