



Premium Elastomeric Pourable Driveway Crack Sealant

Polymer Modified Asphalt Emulsion Based Crack Sealant

- Elastomeric Formula for Outstanding Flexibility & Adhesion
- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- High Solids Formula for Lasting Repair
- Dries Black



Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A polymer modified elastomeric asphalt emulsion crack sealant designed for sealing cracks up to 3/4" wide in asphalt pavement surfaces.

Uses

- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

Surface Preparation

Proper preparation of the crack to be treated is vital to ensuring maximum performance. Use a stiff brush to remove all loose material, dirt, oil, vegetation and existing sealants. Cracks deeper than 1" should be filled with backer-rod or a suitable material to 1/2" depth.

Application

Shake well before using. Using pour spout, pour product into crack slightly above surface level. Material may settle, requiring a second application. Always allow 24 hours between applications.

Drying Time

Depending on weather conditions, Crack Sealant will develop a skinned surface that may be opened to traffic in 1 to 12 hours. However, to assure a traffic-resistant surface, the pavement should be closed to traffic for 12 to 24 hours from application. Always test for trafficability before opening for regular use.

Clean Up

- While wet, use soap and water.
- When Dry, kerosene or mineral spirits.

Weather Conditions

- Apply when temperatures are expected to be above 50 °F for at least 48 hours.
- Do not apply when rain is imminent within 48 hours.

Coverage (Approximate)

- For estimation purposes, up to 150 lineal feet per gallon for cracks 1/2" x 1/4" deep.

Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

Premium Elastomeric Pourable Driveway Crack Sealant
Polymer Modified Asphalt Emulsion Based Crack Sealant

Form No.: JC-TD23751

Packaging

Item #	Container Size	Pack	Weight
23751	.9 Gallon	6	62.3 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Quartz	14808-60-7
Synthetic Rubber	108-18-5
Water	7732-18-5
Alum. Silicate	1332-58-7