



# Clear-Drying Roof Patch

## 100% Acrylic Elastomeric Patching Material

- Acrylic Formula for Lasting Performance
- Excellent Adhesion & Flexibility
- Water Based
- Easy To Apply



Revised: 10/11

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An acrylic, clear drying roof patch designed for repairing cracks, seams, edges around skylights, vents, and metal joints. Dries clear.

### Uses

- Cracks & Seams
- Vents
- Skylights
- Metal Joints

### Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts.

### Application

Apply Roof Patch with a trowel or putty knife. For Tubes, use caulking gun.

### Drying Time

Dependant upon thickness and atmospheric drying conditions. Typically 1 to 4 hours. NOTE - Patch material will reach optimum clarity after several days of curing.

### Clean Up

Wash tools with water before material dries.

### Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature

is expected to drop below 50 °F within a 24 hour period.

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

- Dependent upon depth and width of areas to be repaired.

### Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

### Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Clear-Drying Roof Patch  
100% Acrylic Elastomeric Patching Material

Form No.: JC-TD61771

## Packaging

Item #	Container Size	Pack	Weight
61771	.9 Gallon Pail	6	60 lbs.
61779	10 Oz. Tube	12	10 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic polymer	Proprietary
Ester Alcohol	25265-77-4