



Lap Cement Roof Adhesive

Blind Nailing Cement for Roll Roofing

- A Waterproof Adhesive for Use in the Application of Roll Roofing
- Bonds Layers of Roll Roofing
- Provides a Moisture Barrier
- Manufactured & Tested in Accordance to ASTM D 3409



Revised: 08/17

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A special blend of adhesive asphalts, fibers, special resins and other ingredients that assure its rapid fusion to the base surface. Intended primarily as a blind nailing cement for use with roll roofing. It creates a tight bond and prevents buckling and curling of edges. Roof adhesive is also suitable for application to older roofs to seal cracks and pinholes. Dries black.

Uses

- Adhesive for Rolled Roofing

Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts.

Application

Apply JETCOAT Lap Cement Roof Adhesive with a roofer's brush or a masonry trowel in a uniform consistency. Apply a sufficient amount of adhesive to cover the entire underside of the membrane and to allow a 1/8" – 1/4" bead of adhesive to form along the lap seam when membrane is pressed into place. Broom or walk the overlying sheet firmly into the cement and smooth it out to prevent buckles or blisters.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

Weather Conditions

- Do not apply if rain is imminent within 24 hours of application.

Coverage (Approximate)

- 50 square feet per gallon, 150-175 Linear foot/4 inch Lap.

Precautions

- Do Not Heat or Thin
- Do Not Store at Temperatures Above 100 °F
- Do Not Apply Over Coal Tar Surfaces
- Do Not Apply Where Hydrostatic Pressures Could be Encountered
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 gm/liter max
- Use with Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

This product does not contain any California Proposition 65 Chemicals.

Lap Cement Roof Adhesive
Blind Nailing Cement for Roll Roofing

Form No.: JC-TD62735

Packaging

Item #	Container Size	Pack	Weight
62735	4.75 Gallon Pail	1	44 lbs.
62731	.9 Gallon Pail	6	54 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Magnesium Carbonate	546-93-0
Cellulose	9004-34-6
Amine Salt	Not Est'd