



# GRAY GUARD™ Premium Acrylic Elastomeric Foundation Coating

## Acrylic Elastomeric Emulsion Liquid Rubber Membrane

- Seals & Waterproofs
- Soap & Water Cleanup
- Premium Acrylic Elastomeric Formula
- For Use Above & Below Grade



Revised: 08/17

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An acrylic elastomeric emulsion fortified with water resistant polymers. Forms a liquid rubber membrane that seals and waterproofs a variety of surfaces. Exceptional UV resistance, water resistance, and gray color allow for use above and below grade on surfaces exposed to weather.

### Uses

- Above & Below Grade Exterior Basement Walls
- Poured Concrete Walls
- Polystyrene/Styrofoam Insulation Board
- Wood, Foam & More

### Surface Preparation

For best results, surface shall be clean, dry and free of any dirt or contaminants.

### Application

Stir container thoroughly. Apply GrayGuard using either a brush, trowel, or airless spray unit (suggested tip size .021 to .025). Apply material to a wet film thickness of 60 mil (1.5 mm or .059 inches). To achieve a thickness of 60 mils, apply material at a rate of 150 square feet per 4.75-gallon pail. Allow material to dry and cure for 24 hours prior to application of foam or drainage boards or backfilling.

### Drying Time

Allow 24 hours depending on weather conditions.

### Clean Up

While wet, use soap and water.

### Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24- hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

- Approximately 150 square feet per 4.75 gallon pail at 60 mils thickness.

### Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

### Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

### CALIFORNIA PROPOSITION 65 CHEMICAL WARNING:

This product contains chemicals known to the state of California to cause cancer and birth or developmental defects.

**GRAY GUARD™ Premium Acrylic Elastomeric Foundation Coating**  
Acrylic Elastomeric Emulsion Liquid Rubber Membrane

Form No.: JC-TD64125

## Packaging

Item #	Container Size	Pack	Weight
64125	4.75 Gallon Pail	1	42 lbs.
64121	.9 Gallon Pail	6	52 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	N/A
Titanium Dioxide	13463-67-7
Yellow Oxide	51274-00-1