



GRAY GUARD™ Premium Acrylic Elastomeric Foundation Coating

Acrylic Elastomeric Emulsion Liquid Rubber Membrane

- Seals & Waterproofs
- Soap & Water Cleanup
- Premium Acrylic Elastomeric Formula
- For Use Above & Below Grade



Revised: 10/11

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

An acrylic elastomeric emulsion fortified with water resistant polymers. Forms a liquid rubber membrane that seals and waterproofs a variety of surfaces. Exceptional UV resistance, water resistance, and gray color allow for use above and below grade on surfaces exposed to weather.

Uses

- Above & Below Grade Exterior Basement Walls
- Poured Concrete Walls
- Polystyrene/Styrofoam Insulation Board
- Wood, Foam & More

Surface Preparation

For best results, surface shall be clean, dry and free of any dirt or contaminants.

Application

Stir container thoroughly. Apply GrayGuard using either a brush, trowel, or airless spray unit (suggested tip size .021 to .025). Apply material to a wet film thickness of 60 mil (1.5 mm or .059 inches). To achieve a thickness of 60 mils, apply material at a rate of 150 square feet per 4.75-gallon pail. Allow material to dry and cure for 24 hours prior to application of foam or drainage boards or backfilling.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

While wet, use soap and water.

Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24- hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Approximately 150 square feet per 4.75 gallon pail at 60 mils thickness.

Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

GRAY GUARD™ Premium Acrylic Elastomeric Foundation Coating
Acrylic Elastomeric Emulsion Liquid Rubber Membrane

Form No.: JC-TD64125

Packaging

Item #	Container Size	Pack	Weight
64125	4.75 Gallon Pail	1	42 lbs.
64121	.9 Gallon Pail	6	52 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	N/A
Titanium Dioxide	13463-67-7
Yellow Oxide	51274-00-1