Asphalt Primer

Refined Asphalt Base Coating

- Renews Old Roofing
- For Use Above or Below Grade
- Meets ASTM D 41

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A thin consistency, paint-like product made with refined asphalt and selected petroleum solvents. Adheres to a variety of surfaces. Upon curing, provides an excellent base for JETCOAT asphalt coatings and patching materials.

Uses

- Preserving Roofing Felts
- Preparing Surfaces for Coating

Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts.

Application

Stir container thoroughly before using. Apply to dry surfaces ONLY with brush, roller or sprayer (tip size .017 to .023).

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area.

Weather Conditions

DO NOT apply if rain is imminent within a 24 hour period of application.

Coverage (Approximate)

- Metal Surfaces: 135-150 sq. ft. per gallon
- Concrete and Masonry Surfaces: 75-100 sq. ft. per gallon
- Wood or Composition: 100-125 sq. ft. per gallon
- Worn Roofing: 50-60 sq. ft. per gallon

Precautions

- Do Not Heat or Thin
- Do Not Store Container at Temperatures Above 100 °F
- Do Not Use Where Hydrostatic Pressures May Be Encountered
- Do Not Apply Over Coal Tar Surfaces
- Combustible. Contains Petroleum Distillate

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 Gm/Liter Max
- Use with Adequate Ventilation
- Keep Out of Reach of Children

Revised: 10/11

Asphalt Primer
Refined Asphalt Base Coating

Form No.: JC-TD64135

Packaging

Item #	Container Size	Pack	Weight
64135	4.75 Gallon	1	43 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7

Copyright © 2008, JETCOAT
All rights reserved.

472 S. Brehl Avenue • Columbus, Ohio 43223
Phone: 800-394-0047 • Fax: 614-279-7201

Form No.: JC-TD64135
Revised: 10/11