



COOL KING® 7-Year Premium Fibered Aluminum Roof Coating

Energy Saving Aluminum Sealant

- 7-Year Protection
- Bright Aluminum Color
- Saves Energy
- Superior Reflectivity
- Our Best Aluminum Roof Coating
- Meets ASTM D 2824-04 Type III & D 1227 Type III



Revised: 08/17

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

This premium energy saving formula stays brighter longer. It will seal, protect, and reflect solar heat using a proven blend of selected waterproofing pigments. Forms an excellent adhesive bond with most substrates. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, heat is reflected back into the building, saving energy costs. Dries bright silver.

Uses

- Metal & Concrete Roofs
- Weathered Asphalt
- Metal Buildings/Grain Bins
- Built-Up Roofs & Mobile Homes
- Mod. Bitumen, SBS & APP

Surface Preparation

Repair all cracks, splits, and holes using JETCOAT All-Weather Roof Patch and Resin Treated Multi-Purpose Reinforcing Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

Application

Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not

apply to wet or damp surfaces. Do not apply to roofs which hold water. Standing water will result in premature failure.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean up with waterless hand cleaner immediately after use.

Weather Conditions

- Do not apply if rain or heavy dew is expected within 24 hours of application.
- Do not apply if temperature is expected to fall below 50 °F. within 12 hours of application.

Coverage (Approximate)

- Metal Roofs: 75-100 sq. ft. per gallon
- Composition Roofs: 50-75 sq. ft. per gallon

Precautions

- Do Not Heat or Thin
- Do Not Store at Temperatures Above 100 °F
- Combustible. Contains Petroleum Distillate

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 370 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

This product does not contain any California Proposition 65 Chemicals.

Cool King® 7-Year Premium Fibered Aluminum Roof Coating
Energy Saving Aluminum Sealant

Form No.: JC-TD65255

Packaging

Item #	Container Size	Pack	Weight
65255	4.75 Gallon Pail	1	49 lbs.
65251	.9 Gallon Pail	6	58 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Stoddard Solvent	64742-88-7
Aluminum Flake	7429-90-5
Cellulose	9004-34-6
Calcium Carbonate	1317-65-3