



# COOL KING® 7-Year White Reflective Elastomeric Roof Coating

Forms a High Solids Rubber-Like Membrane

- 7-Year Protection
- Dries White
- Energy Star Rated
- Saves Energy
- Acrylic Elastomeric Polymers for Lasting Durability



Revised: 08/17

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An acrylic elastomeric roof coating designed to form a rubber-like membrane over a variety of roof surfaces. Reflects the sun's rays resulting in energy cost savings. Designed for use on metal, polyurethane foam, masonry, asphalt and wood surfaces. Dries white.

### Uses

- Aged Asphalt & Aluminum Coatings
- Polyurethane Foam
- Mobile Homes, Campers/RV's
- Metal, Concrete, Wood & More

### Surface Preparation

Clean Roof - Sweep off all dirt, dust, and debris. Remove rust, mildew, oil, grease, or other foreign material on the surface. Allow freshly applied asphalt roofs to cure a minimum of 4 weeks prior to applying this coating. Scrub roof with roof cleaner or bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry.

### Application

**APPLYING ROOF COATING:** Stir pail thoroughly. Do not dilute. For best results apply White Elastomeric Roof Coating with a soft brush, 3/4" nap paint roller, or high pressure sprayer (Tip Size: .021 to .025). For optimum performance, durability and warranty purposes, apply a second coat.

**NOTE:** This product is not recommended for gravel, dead level (flat), or shingled roof surfaces.

### Drying Time

Dries to the touch in 2-3 hours. Allow 6-8 hours before applying a second coat.

### Clean Up

Wash tools with water before material dries.

### Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

- One 4.75-gallon pail will coat approximately 250-350 square feet of roof surface per coat. Two coats are recommended.

### Precautions

- Do Not Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

### Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

**Cool King® 7-Year White Reflective Elastomeric Roof Coating**  
Forms a High-Solids Rubber-Like Membrane

Form No.: JC-TD66205

**CALIFORNIA PROPOSITION 65 CHEMICAL WARNING:**

This product contains chemicals known to the state of California to cause cancer and birth or developmental defects.

**Packaging**

Item #	Container Size	Pack	Weight
66205	4.75 Gallon Pail	1	55 lbs.
66201	.9 Gallon Pail	6	69 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Limestone	16389-88-1
Titanium Dioxide	13463-67-7
Ester Alcohol	25265-77-4