



COOL KING® 5-Year White Reflective Roof Coating

Acrylic Fortified Reflective Coating

- 5-Year Protection
- Dries White
- Saves Energy



Revised: 08/17

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

Acrylic fortified white reflective roof coating designed to cool roofs and provide energy cost savings. Designed for use on a variety of roof surfaces.

Uses

- Mobile Homes/RV's
- Metal, Concrete, Wood & More

Surface Preparation

Clean Roof - Sweep off all dirt, dust, and debris. Remove rust, mildew, oil, grease, or other foreign material on the surface. Allow freshly applied asphalt roofs to cure a minimum of 4 weeks prior to applying this coating. Scrub roof with roof cleaner or bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry.

Application

APPLYING ROOF COATING: Stir pail thoroughly. Do not dilute. For best results apply White Roof Coating with a soft brush, 3/4" nap paint roller, or high pressure sprayer (Tip Size: .021 to .025). For optimum performance, durability and warranty purposes, apply a second coat.

NOTE: This product is not recommended for gravel, dead level (flat), or shingled roof surfaces.

Drying Time

Dries to the touch in 2-3 hours. Allow 6-8 hours

before applying a second coat.

Clean Up

Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- One 4.75-gallon pail will coat approximately 250-350 square feet of roof surface per coat. Two coats are recommended.

Precautions

- Do Not Thin
- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Cool King® 5-Year White Reflective Roof Coating
Acrylic Fortified Reflective Coating

Form No.: JC-TD66235

CALIFORNIA PROPOSITION 65 CHEMICAL WARNING:

This product contains chemicals known to the state of California to cause cancer and birth or developmental defects.

Packaging

Item #	Container Size	Pack	Weight
66235	4.75 Gallon Pail	1	55 lbs.
66231	.9 Gallon Pail	6	69 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Limestone	16389-88-1
Titanium Dioxide	13463-67-7
Ester Alcohol	25265-77-4