



# Premium Aluminum Paint

## Resin Based Protective Paint

- Outstanding Reflectivity
- Long-Term Durability
- Lustrous Aluminum Finish
- Cools Interior Building & Structure Temperature
- Weatherproofs



**Premium Aluminum Paint**  
Resin Based Protective Paint

Form No.: JC-TD66455

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

A premium resin based aluminum protective paint that exhibits a brilliant silver color for superior reflectivity. Protects a variety of metal surfaces including grain bins, silos, roofs, chain link fences and more. Can also be applied to wood, concrete and other building substrates where enhanced reflectivity is desired. Dries bright silver.

### Uses

- Grain Bins/Silos
- Metal Roofs & Fences
- Tanks & Trailers
- Dairy Equipment
- Metal & Wood Surfaces

### Surface Preparation

Surface to be painted shall be clean and dry. All rust should be wire brushed to remove any loose particles. Sand glossy areas to improve adhesion.

### Application

Stir aluminum thoroughly when beginning and stir again every 15 minutes as aluminum paints tend to settle rapidly. Brush in one direction and do not over brush as this will disturb the leafing qualities of the aluminum. Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size .017 to .023). Although paint will cover in one coat, a second coat may be applied for optimum performance and durability.

### Drying Time

Allow 24 hours depending on weather conditions.

### Clean Up

Clean tools with mineral spirits in a well ventilated area immediately after use.

### Weather Conditions

- Application temperature must be a minimum of 50 °F and rising.
- Do not apply when temperature is expected to drop below 50 °F within a 24-hour period.
- Do not apply if rain is imminent within 24 hours of application.

### Coverage (Approximate)

- Up to 180 square feet per gallon.
- Up to 1,000 square feet per 4.75 gallon pail.

### Precautions

- Do Not Heat Or Thin
- Do Not Store At Temperatures Above 100 °F
- Combustible. Contains Petroleum Distillate

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 450 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN



## Packaging

Item #	Container Size	Pack	Weight
66455	4.75 Gallon Pail	1	49 lbs.
66451	.9 Gallon Pail	6	59 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Mineral Spirits	64742-88-7
Petroleum Resin	N/A
Bodied Linseed Oil	67745-08-5
Aluminum Paste	7429-90-5