



# 5-Year Fibered Aluminum Roof Coating

## Bright Aluminum Color



- 5-Year Protection
- Saves Energy & Reflects Heat
- Bright Aluminum Color
- Ideal for Use on Farm Buildings, Mobile Homes & RV's

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

A blend of select asphalts, fibers and aluminum pigments. This material will reflect up to 80% of the sun's rays, helping prevent excessive drying and cracking of substrate, thus reducing leaks. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, inside heat is reflected back into the building, saving energy costs.

### Uses

- Agricultural Buildings, Silos & Grain Bins
- Metal & Built-up Roofs
- Weathered Asphalt Coatings
- Mobile Homes/RV's
- Mod. Bitumen, SBS/APP

### Surface Preparation

Repair all cracks, splits, and holes using JETCOAT All Weather Roof Cement and Asphalt Coated Reinforcing Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

### Application

Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not

apply to roofs which hold water. Standing water will result in premature failure.

### Drying Time

Up to 24 hours depending on weather conditions .

### Clean Up

Clean up with waterless hand cleaner immediately after use.

### Weather Conditions

- Do not apply if rain or heavy dew is expected within 24 hours of application.
- Do not apply to wet or damp surfaces.
- Do not apply if temperature is expected to fall below 50 °F within 12 hours of application.

### Coverage (Approximate)

- Metal Roofs: 75-100 sq. ft. per gallon
- Composition Roofs: 50-75 sq. ft. per gallon

### Precautions

- Do Not Heat Or Thin
- Do Not Store Container At Temperatures Above 100 ° F
- Combustible. Contains Petroleum Distillate



5-Year Fibered Aluminum Roof Coating  
Bright Aluminum Color

Form No.: JC-TD66475

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 370 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out Of Reach Of Children

## Packaging

Item #	Container Size	Pack	Weight
66475	4.75 Gallon Pail	1	49 lbs.
66471	.9 Gallon Pail	6	58 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Stoddard Solvent	64742-88-7
Aluminum Flake	7429-90-5
Cellulose	9004-34-6
Calcium Carbonate	1317-65-3