



# White Elastomeric Roof Patch

## Acrylic Emulsion Patch Material

- Acrylic Elastomeric Polymers for Long Lasting Flexibility
- Outstanding Durability
- Easy To Apply



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An acrylic emulsion patch material designed for repairing cracks, seams, edges around skylights, vents, and metal joints. Dries white.

### Uses

- Patching Cracks
- Filling Holes
- Repairing Flashings, Vents, Gutters, & Air Conditioners

### Surface Preparation

Clean Roof - Sweep off all dirt, dust, and debris. Remove rust, mildew, oil, grease, or other foreign material on the surface. Scrub roof with solution of TSP (Trisodium Phosphate) and water. Remove mold and mildew with bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry.

### Application

• Stir pail thoroughly. With a 4-inch wide paint brush, apply a liberal amount of Elastomeric Roof Patch. Apply Roof Patch 6-inches wide along cracks, seams, or vent areas. Roll Reinforcing Fabric into wet roof patch. Smooth out fabric with paint brush. While material is still wet, brush another coat of Roof Patch over the Reinforcing Fabric. Make certain the fabric is completely embedded into Roof Patch material. Allow Roof Patch material to dry thoroughly before applying White Elastomeric Roof Coating.

### Drying Time

Dependent on depth of repairs. Typically dries within 24 hours.

### Clean Up

Wash tools with water before material dries.

### Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

Dependent upon depth and width of areas to be repaired.

### Precautions

- Do Not Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use



**White Elastomeric Roof Patch**  
Acrylic Emulsion Patch Material

Form No.: JC-TD66501

- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

### Packaging

Item #	Container Size	Pack	Weight
66501	.9 Gallon Pail	6	71 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	Proprietary
Limestone	16389-88-1
Titanium Dioxide	13463-67-7
Ester Alcohol	25265-77-4