



# Fibered Roof & Foundation Coating

## Water Resistant Asphalt Based Coating

- Seals, Protects & Waterproofs
- Use Above or Below Grade
- Meets ASTM D 4479



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

A mixture of liquid asphalt and fibers designed to form a tough, adhesive bond with most roof surfaces. This material will seal small cracks, joints, seams and nail holes. Highly resistant to water and other types of weather damage. Dries black.

### Uses

- Metal Roofs
- Concrete Roofs
- Built-Up Roofs
- Concrete Foundations
- Roof Felts, Wood Roofs & More

### Surface Preparation

Clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with JETCOAT All Weather Roof Cement and JETCOAT Asphalt Coated Reinforcing Fabric repair material.

### Application

Coat entire surface area with JETCOAT Fibered Roof and Foundation Coating. For best results, apply a uniform coating with roofing brush when surface is dry. One coat provides year round protection.

### Drying Time

Up to 24 hours depending on weather conditions.

### Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

### Weather Conditions

- Do not apply if rain or heavy dew is expected within 24 hours of application.

### Coverage (Approximate)

- Metal Roofing: 60-70 sq. ft. per gallon
- Felt or Composition: 50-60 sq. ft. per gallon
- Concrete or Masonry Surfaces: 25-50 sq. ft. per gallon
- Strip Composition or Dried Out Roofing: 25-50 sq. ft. per gallon

### Precautions

- Do Not Heat Or Thin
- Do Not Store Container At Temperatures Above 100 ° F
- Combustible. Contains Petroleum Distillate
- Do Not Use Where Hydrostatic Pressures May Be Encountered.
- Do Not Apply Over Coal Tar Surfaces

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet



**Fibered Roof & Foundation Coating**  
Water Resistant Asphalt Based Coating

Form No.: JC-TD66515

- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 250 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out Of Reach Of Children

### Packaging

Item #	Container Size	Pack	Weight
66515	4.75 Gallon Pail	1	44 lbs.
66511	.9 Gallon Pail	6	52 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Cellulose Fibers	9004-34-6
Magnesium Carbonate	546-93-0