



All-Weather Roof Cement

Water Repellent Sealing Compound

- Bonds Rapidly To Wet, Moist & Cold Surfaces
- Ideal For Use On Vent Pipes & Skylights
- Meets ASTM D 4586 and D 3409



Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A thick blend of liquid asphalt and fibers specially designed as a patching material, adhesive and general utility sealing compound that imparts water-repellency to flashings, seams or patches in roofs and gutters.

Uses

- Splits and Seams
- Flashings
- Vents
- Skylights
- Metal Joints
- Chimneys
- Coping

Surface Preparation

Clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts.

Application

Apply material with a mason's trowel to about 1/8" thick, smoothing down all edges. Mend large cracks, breaks, or loose seams by applying cement to defective area. Extend cement to three inches beyond area to be repaired. Spot stick Reinforcing Fabric repair material in position over entire area and apply an additional layer of cement. Leaks around vent pipes, spouts, valleys, skylights, chimneys and flashings can be made weather tight by applying JETCOAT All Weather Roof Cement.

Drying Time

Up to 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

Weather Conditions

- Can be used in wet or dry conditions.

Coverage (Approximate)

- 12 square feet per gallon at 1/8 inches thick.

Precautions

- Do Not Heat Or Thin
- Do Not Store Container At Temperatures Above 100 ° .
- Combustible. Contains Petroleum Distillate
- Do Not Use Where Hydrostatic Pressures May Be Encountered.
- Do Not Apply Over Coal Tar Surfaces

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out Of Reach Of Children



All-Weather Roof Cement
Water Repellent Sealing Compound

Form No.: JC-TD66535

Packaging

Item #	Container Size	Pack	Weight
66535	4.75 Gallon Pail	1	50 lbs.
66531	.9 Gallon Pail	6	56 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Cellulose Fibers	9004-34-6
Magnesium Carbonate	546-93-0