



Concrete Patch

100% Acrylic Formula for Tough, Durable Repairs



- 100% Acrylic Formulation
- Fills Cracks Up To 1" Wide
- Heavy-Bodied Trowel Grade Formula
- Repairs Damaged & Spalled Areas Up to 1/4" Deep

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A 100% acrylic heavy-bodied trowel grade crack filler designed for filling larger cracks up to 1" wide in concrete surfaces. Concrete Patch can also be used to fill and repair damaged and spalled areas in concrete up to 1/4" deep.

Uses

- Use to Repair Concrete Driveways, Floors, Patios, Sidewalks, Pool Decks, & More

Surface Preparation

- **Cleaning Cracks** - Remove dirt and vegetation from cracks with screwdriver or other suitable instrument. Flush out crack with water and allow to dry.
- **Damaged and Spalled Areas** - Remove dirt and debris from repair area. Scrub thoroughly with wire brush and rinse with water.

Application

Apply material with rectangular trowel or wide putty knife. Spread and smooth out material flush to adjoining surface.

Drying Time

Allow material to dry and cure for 48 hours prior to resuming foot or vehicle traffic.

Clean Up

- Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Dependent upon depth and width of repair.

Precautions

- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 gm/liter max
- KEEP OUT OF REACH OF CHILDREN



Concrete Patch
100% Acrylic Formula for Tough, Durable Repairs

Form No.: JC-TD66711

Packaging

Item #	Container Size	Pack	Weight
66711	.9 Gallon Pail	6	99.8 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	Proprietary
Fiber	9004-34-6
Ester Alcohol	25265-77-4
Silicon Dioxide	14808-60-7