



# High Gloss Sealer

## Advanced Water-Based Acrylic Emulsion Sealer

- Dries to a Clear Glossy Finish
- 100% Acrylic Formula
- Fast Drying
- Durable Lasting Finish



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An advanced water-based acrylic clear sealer that provides a high gloss protective and durable finish to paving stone and exposed aggregate surfaces.

### Uses

- Paving Stone, Decorative Stone, and Exposed Aggregate Concrete

### Surface Preparation

• Clean Surface - Sweep all dirt and loose debris from surface. Remove all oil, grease and foreign materials. Surface must be completely dry before applying High Gloss Sealer.

### Application

Stir pail thoroughly. Apply thin even coats of sealer with a roller. Additional coats may be applied to achieve desired level of gloss and finish. Allow material to dry thoroughly between coats.

### Drying Time

Allow 2-3 hours to dry, depending on weather conditions.

### Clean Up

- Wash tools with water before material dries.

### Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a

24- hour period.

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

- 130 to 170 square feet per gallon per coat. A 4.75 gallon pail will cover approximately 600-800 square feet.

### Precautions

- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

High Gloss Sealer  
Advanced Water-Based Acrylic Emulsion Sealer

## Packaging

Item #	Container Size	Pack	Weight
66815	4.75 Gallon Pail	1	46 lbs.
66811	.9 Gallon Pail	6	55 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	Proprietary