



Concrete Bonding Agent & Fortifier

Professional Grade Repair Strengthener

- Increases UV, Chemical & Water Resistance
- Strengthens Concrete Repairs & Overlays
- Adheres New Concrete to Old
- Increases Flexibility



Revised: 08/17

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A professional grade bonding agent & fortifier for concrete designed to strengthen concrete patches and aid in the adhesion of new concrete.

Uses

- Concrete Patches, Repairs & Overlays

Surface Preparation

• **Clean Concrete Surface** - Sweep all dirt and loose debris from concrete surface. Scrub all oil and gasoline stains with household detergent and water. Rinse off entire concrete surface with water and allow to dry thoroughly before applying concrete sealer.

Application

Mixing: Stir contents before using.

- **Concrete Patching:** Mix Concrete Fortifier full strength with dry concrete, mortar, stucco or other dry material.

- **Bonding Agent:** Mix 2 parts Concrete Fortifier to 1 part water. Apply to slightly damp surface. Apply concrete or patching mixes immediately while the bonding agent is still wet. Caution: Do not allow bonding agent to dry before placing concrete or patching mixes over it.

Drying Time

Allow mixes containing Concrete Fortifier to dry for 24 to 48 hours.

Clean Up

- Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Dependent upon dilution rate with water.

Precautions

- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

This product does not contain any California Proposition 65 Chemicals.

Concrete Bonding Agent & Fortifier
Professional Grade Repair Strengthener

Form No.: JC-TD66854

Packaging

Item #	Container Size	Pack	Weight
66854	.9 Quart Bottle	12	30 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	Proprietary