




# Premium One Coat 100% Acrylic Barn & Fence Paint- Green

Livestock Friendly, Fade Resistant Paint



Revised: 01/15

- Acrylic Water-Based Formula
- Resists Fading, Peeling & Chipping
- Environmentally Friendly Formula
- Helps Prevent Cribbing
- Livestock Safe - Dry Finish

- Mold-Resistant
- Easy Soap & Water Cleanup
- Dries to a Semi-Gloss Finish

### Manufacturer:

JETCOAT  
 472 Brehl Avenue  
 Columbus, Ohio  
 Phone: 800-394-0047  
 Fax: 614-279-7201  
 www.JETCOATinc.com

### Description

A premium fade resistant 100% acrylic paint fortified with UV inhibitors for years and years of lasting durability. Easily applied by spray, brush or roller. Features one coat coverage. Available in Traditional Barn Green, Brown, Red, Gray, White and Black.

### Uses

- All Wood Plank Fences
- All Types of Barns
- Roofs, Concrete & More

### Surface Preparation

Surface shall be clean, dry and free of any dirt or contaminants.

### Application

Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size .017 to .021).

### Drying Time

Dry to the touch in 2-3 hours. Allow 6-8 hours before applying second coat.

### Clean Up

Wash tools with water before material dries.

### Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour

period.

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

- Approximately 95-100 square feet per gallon per coat depending upon porosity of surface.
- A 4.75 - gallon pail will cover approximately 450-475 square feet per coat.

### Precautions

- Do Not Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN
- WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Premium One Coat 100% Acrylic Barn & Fence Paint- Green  
 Livestock Friendly, Fade Resistant Paint



Form No.: JC-TD66395

## Packaging

Item #	Container Size	Pack	Weight
66391T	275 Gallon Tote	1	2589 lbs.
66397D	55 Gallon Drum	1	530 lbs.
66395	4.75 Gallon Pail	1	47.5 lbs.
66391	.9 Gallon Pail	6	58 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Limestone	16389-88-1
Chrome Oxide	1308-38-9
Black Oxide	1317-61-9