



# Premium Elastomeric Pourable Driveway Crack Sealant

Polymer Modified Asphalt Emulsion Based Crack Sealant

- Elastomeric Formula for Outstanding Flexibility & Adhesion
- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- High Solids Formula for Lasting Repair
- Dries Black



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

A polymer modified elastomeric asphalt emulsion crack sealant designed for sealing cracks up to 3/4" wide in asphalt pavement surfaces.

### Uses

- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

### Surface Preparation

Proper preparation of the crack to be treated is vital to ensuring maximum performance. Use a stiff brush to remove all loose material, dirt, oil, vegetation and existing sealants. Cracks deeper than 1" should be filled with backer-rod or a suitable material to 1/2" depth.

### Application

Shake well before using. Using pour spout, pour product into crack slightly above surface level. Material may settle, requiring a second application. Always allow 24 hours between applications.

### Drying Time

Depending on weather conditions, Crack Sealant will develop a skinned surface that may be opened to traffic in 1 to 12 hours. However, to assure a traffic-resistant surface, the pavement should be closed to traffic for 12 to 24 hours from application. Always test for trafficability before opening for regular use.

### Clean Up

- While wet, use soap and water.
- When Dry, kerosene or mineral spirits.

### Weather Conditions

- Apply when temperatures are expected to be above 50 °F for at least 48 hours.
- Do not apply when rain is imminent within 48 hours.

### Coverage (Approximate)

- For estimation purposes, up to 150 lineal feet per gallon for cracks 1/2" x 1/4" deep.

### Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

This product does not contain any California Proposition 65 Chemicals.

Premium Elastomeric Pourable Driveway Crack Sealant  
Polymer Modified Asphalt Emulsion Based Crack Sealant

Form No.: JC-TD23751

## Packaging

Item #	Container Size	Pack	Weight
23751	.9 Gallon	6	62.3 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Quartz	14808-60-7
Synthetic Rubber	108-18-5
Water	7732-18-5
Alum. Silicate	1332-58-7