



# All-Weather Pothole Patch

## Rapid Setting



Revised: 03/11

- Works in All Temperatures
- Works in Wet or Dry Conditions
- Immediately Ready for Traffic
- Easy to Apply- Just Pour & Tamp

### Manufacturer:

JETCOAT  
 472 Brehl Avenue  
 Columbus, Ohio  
 Phone: 800-394-0047  
 Fax: 614-279-7201  
 www.JETCOATinc.com

### Description

JETCOAT All-Weather Pothole Patch is a rapid setting pothole patch designed for filling potholes and depressions in driveways, parking lots, roads, and other pavement surfaces. It can be used in both wet and dry conditions.

### Uses

For Driveways, Parking Lots, Roads, & Other Pavement Surfaces.

### Surface Preparation

Remove loose materials and debris from pothole.

### Application

Fill pothole or depression to a height of 1/2 inch above surrounding pavement. For deeper depressions apply in 2 inch lifts and tamp, repeat until filled. Tamp into place with a shovel, hand tamper or vehicle tire.

*Note: If material is too hard, place in warm room or open bag and place in direct sunlight until soft*

### Drying Time

Immediately ready for traffic.

### Clean Up

- When dry, kerosene or mineral spirits.

### Weather Conditions

- Works in all Temperatures
- Works in Wet or Dry Conditions

### Coverage (Approximate)

- 5 sq. ft. at 1" Thickness.

### Safety and Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- KEEP OUT OF REACH OF CHILDREN

### Packaging

Item #	Container Size	Pack	Weight
23753	50 lb Bag	1	50 lbs.

Ingredients:	Cas No.
Aggregate	1317-65-3
Modified Asphalt Cement	8052-42-4
Petroleum Distillate	68476-30-2

**All-Weather Pothole Patch**  
 Rapid Setting

**Form No.: JC-TD23753**

