## Technical Data Sheet



# Premium One Coat 100% Acrylic Barn & Fence Paint- Black

Livestock Friendly, Fade Resistant Paint

- Acrylic Water-Based Formula
- Resists Fading, Peeling & Chipping
- Environmentally Friendly Formula
- Helps Prevent Cribbing
- Livestock Safe Dry Finish

#### Manufacturer:

JETCOAT 472 Brehl Avenue Columbus, Ohio Phone: 800-394-0047 Fax: 614-279-7201 www.JETCOATinc.com

#### **Description**

A premium fade resistant 100% acrylic paint fortified with UV inhibitors for years and years of lasting durability. Easily applied by spray, brush or roller. Features one coat coverage. Available in Traditional Barn Red, Gray, White and Black.

#### Uses

- All Wood Plank Fences
- All Types of Barns
- Roofs, Concrete & More

#### **Surface Preparation**

Surface shall be clean, dry and free of any dirt or contaminants.

#### **Application**

Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size .017 to .021).

#### **Drying Time**

Dry to the touch in 2-3 hours. Allow 6-8 hours before applying second coat.

#### **Clean Up**

Wash tools with water before material dries.

#### **Weather Conditions**

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.
- In areas where dew or fog accumulates in the

- Mold-Resistant
- Easy Soap & Water Cleanup
- Dries to a Semi-Gloss Finish



- early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

#### **Coverage (Approximate)**

- Approximately 95-100 square feet per gallon per coat depending upon porosity of surface.
- A 4.75 gallon pail will cover approximately 450-475 square feet per coat.

#### **Precautions**

- Do NotThin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F


#### **Safety And Environmental Precautions**

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN
- WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.



Premium One Coat 100% Acrylic Barn & Fence Paint- Black Livestock Friendly, Fade Resistant Paint

Revised: 12/09



### Packaging

ltem #	Container Size	Pack	Weight
66418T	275 Gallon Tote	1	2494 lbs.
66417D	55 Gallon Drum	1	511 lbs.
66415	4.75 Gallon Pail	1	47.5 lbs.
66411	.9 Gallon Pail	6	58 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.	
Water	7732-18-5	
Acrylic Emulsion Polymer	Proprietary	
Limestone	16389-88-1	
Black Oxide	1317-61-9	

Copyright © 2008, JETCOAT All rights reserved. 472 S. Brehl Avenue • Columbus, Ohio 43223 Phone: 800-394-0047 • Fax: 614-279-7201 Form No.: JC-TD66415 Revised: 12/09

www.JETCOATinc.com