



Non-Fibered Roof, Fence & Foundation Coating

Asphalt Based Sealer/Preservative

- Penetrates, Preserves & Protects most Flat Roofs, Foundations, Wood Fences, Barns & More
- Use Above or Below Grade
- Meets ASTM D 41



Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

This sealer/preservative is an excellent saturant for excessively dry composition roofing. It will add years of service as it rust proofs metal, preserves wood, damp proofs stone or brick and rejuvenates composition surfaces. May be used to coat concrete foundations, above and below grade. Ideal for use as a fence and barn coating.

Uses

- Concrete Foundations
- Most Flat Roof Surfaces
- Wood Fences & Barns
- Metal, Concrete, Wood & More

Surface Preparation

Clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with JETCOAT All-Weather Roof Cement and JETCOAT Asphalt Coated Reinforcing Fabric repair material.

Application

Do not apply to sloped roof surfaces, as product may run or drip. Coat entire surface area with JETCOAT Non-Fibered Roof, Fence and Foundation Coating. Material may be brushed or rolled. Porous surfaces may require two applications. Do not apply on any wet surface.

Drying Time

Up to 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

Weather Conditions

- Do not apply if rain or heavy dew is expected within 24 hours of application.

Coverage (Approximate)

- Metal Surfaces: 90-100 sq. ft. per gallon
- Concrete & Masonry Surfaces: 75-100 sq. ft. per gallon
- Wood or Composition: 65-90 sq. ft. per gallon
- Worn Roofing: 50-80 sq. ft. per gallon

Precautions

- Do Not Heat or Thin
- Do Not Store Container at Temperatures Above 100 °F
- Combustible. Contains Petroleum Distillate
- Do Not Use Where Hydrostatic Pressures May be Encountered.
- Do Not Apply Over Coal Tar Surfaces

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet



Non-Fibered Roof, Fence & Foundation Coating
Asphalt Based Sealer/Preservative

Form No.: JC-TD66525

- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out Of Reach Of Children

Packaging

| Item # | Container Size | Pack | Weight |
|--------|------------------|------|---------|
| 66525 | 4.75 Gallon Pail | 1 | 42 lbs. |
| 66521 | .9 Gallon Pail | 6 | 47 lbs. |

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

| Ingredients: | Cas No. |
|-------------------|------------|
| Petroleum Asphalt | 8052-42-4 |
| Mineral Spirits | 64742-88-7 |