



# Acrylic Fence & Barn Paint

## Environmentally Friendly Formula

- Acrylic, Water-Based Formula
- Resists Fading, Peeling & Weathering
- Environmentally Friendly Formula
- Easy Soap & Water Cleanup
- Mold Resistant
- Dries Black



Revised: 04/12

### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

Quality acrylic fence paint designed to beautify and protect wood plank fences, barns and more. Environmentally friendly water-based formula.

### Uses

- All wood plank fences
- All types of barns
- Roofs, concrete, and more

### Surface Preparation

Surface shall be clean, dry and free of any dirt or contaminants.

### Application

Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size is a minimum of .017 to .021).

### Drying Time

Dry to the touch in 2-3 hours. Allow 6-8 hours before applying second coat.

### Clean Up

Clean tools with soap and water before material has dried.

### Weather Conditions

Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period. In areas where dew or fog accumulates in

the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

Up to 95-100 square feet per gallon per coat depending upon porosity of surface

### Precautions

- Do Not Heat or Thin
- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

### Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply in a Well Ventilated Area
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/Liter
- Keep Out of Reach of Children
- Avoid Breathing Vapors and Contact with Eyes and Skin. Do Not Take Internally
- Wear Eye Protection and Gloves When Applying
- Warning: This Product Contains Chemicals Known to The State of California to Cause Cancer and Birth Defects or Other Reproductive Harm



**FARM PRIDE™**  
Seal Of Approval

**Acrylic Fence & Barn Paint**  
Environmentally Friendly Formula

Form No.: JC-TD66765

## Packaging

Item #	Container Size	Pack	Weight
66767D	55 Gallon Drum	1	511 lbs.
66765	4.75 Gallon Pail	1	46 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Acrylic Emulsion Polymer	(Proprietary)
Carbon Black	1333-86-4
Ethylene Glycol	107-21-1
Texanol	25265-77-4